

DOWNLIGHT enI-DL860



The DL860 is a quality high CRI, low glare LED Downlight with a wide range of power options and beam angles. Designed for general lighting with specific uses for retail and hotels.

FEATURES

- High CRI greater than 90
- Supplied with 1.2m flex & plug

OPTIONS

- Multiple power options
- Multiple Optics (beam angles)
- Dali Controls




DOWNLIGHT enl-DL860

PRODUCT RANGE

| Model # | Rated Power (W) | Luminous Flux (lm) | Dimensions(mm) | | | | Cutout | Weight (kg) |
|-------------------------|-----------------|--------------------|----------------|-----|-----|-----|----------|-------------|
| | | | A | B | C | D | | |
| enl-DL860-7-xyy-zz | 7 | 630 | 85 | 56 | 62 | 68 | Ø68-75 | 0.2 |
| enl-DL860-10-xyy-zz | 10 | 1040 | 110 | 75 | 85 | 90 | Ø90-100 | 0.3 |
| enl-DL860-13-xyy-zz | 13 | 1250 | 150 | 97 | 115 | 119 | Ø120-130 | 0.4 |
| enl-DL860-18-xyy-zz-150 | 18 | 1800 | | | | | | |
| enl-DL860-18-xyy-zz-170 | 18 | 1950 | 170 | 112 | 135 | 139 | Ø140-150 | 0.6 |
| enl-DL860-25-xyy-zz-170 | 25 | 2750 | | | | | | |
| enl-DL860-18-xyy-zz-190 | 18 | 1950 | 190 | 120 | 156 | 157 | Ø160-170 | 0.7 |
| enl-DL860-25-xyy-zz-190 | 25 | 2750 | | | | | | |
| enl-DL860-30-xyy-zz | 30 | 3200 | 240 | 142 | 191 | 194 | Ø195-230 | 0.9 |
| enl-DL860-18-xyy-zz-240 | 18 | 1900 | | | | | | |
| enl-DL860-25-xyy-zz-240 | 25 | 2750 | | | | | | |
| enl-DL860-35-xyy-zz | 35 | 3650 | | | | | | |
| enl-DL860-40-xyy-zz | 40 | 4250 | | | | | | |

x stands for CRI. Use 8 for Ra>80 or 9 for Ra>90
 yy stands for CCT. Use 27 for 2700K, 30 for 3000K, 40 for 4000K or 50 for 5000K.
 zz stands for Beam Angle. Use 24, 36, 55 (only 7W) or 60 for beam angle.
 DALI dimmable options available on request

DIMENSIONS



COMPLIANCE

The enl-DL860 meets all relevant standards and regulatory requirements.



TECHNICAL INFORMATION

Optical

| | |
|--------------------|---------------------|
| Light source | LED |
| CRI | Ra>90 |
| Beam Angle | 24°, 36°, 55°, 60° |
| CCT | 3000K, 4000K, 5000K |
| Luminaire efficacy | Up to 100lm/W |

Electrical

| | |
|-------------------------------|------------------------|
| Power consumption | 7W - 40W |
| Operating voltage & frequency | 220-240 VAC , 50/60 Hz |
| Power factor | >0.9 |

Environmental

| | |
|-----------------------------|---|
| IP rating | IP44(Below Ceiling), IP20(Inside Ceiling) |
| Ambient temperature range | -20°C to + 45°C |
| Material Composition (body) | ADC12 Aluminium Die-casting |
| Fixture Colour | White (RAL9016) |

Expected Lifespan >54,000hrs @L70

Warranty* 5 years

Data subject to change without notice
 * Refer to warranty policy